



EPM-S150S 系列概述

一. 电源规格:

电源型号 (MODEL)	输入(VAC)	输出 (VDC)	保护功能 (PROTECTION)	尺寸 (SIZE) MM
EPM-S150S5	90-132VAC' 176-264VAC	5V/25A	SCP/OCP/LVP	198mm*98mm*39mm
EPM-S150S12	90-132VAC' 176-264VAC	12V/12.5A	SCP/OCP/LVP	198mm*98mm*39mm
EPM-S150S15	90-132VAC' 176-264VAC	15V/10A	SCP/OCP/LVP	198mm*98mm*39mm
EPM-S150S24	90-132VAC' 176-264VAC	24V/6.25A	SCP/OCP/LVP	198mm*98mm*39mm
EPM-S150S28	90-132VAC' 176-264VAC	28V/5.5A	SCP/OCP/LVP	198mm*98mm*39mm
EPM-S150S36	90-132VAC' 176-264VAC	36V/4.2A	SCP/OCP/LVP	198mm*98mm*39mm
EPM-S150S48	90-132VAC' 176-264VAC	48V/3.2A	SCP/OCP/LVP	198mm*98mm*39mm

二. 系列特性:

Features

- Compact size
- Protections: SCP / OCP/LVP
- High efficiency
- Low cost, high reliability
- 100% full load burn-in test
- 1 years warranty

三. 产品外观:




Net weight: 680g



四. 工作温度，输出功率曲线:

Temperature- load curve



五. 测试标准:

EMC DATA:

1、 EMI

RE/CE	EN55022 CLASS A
Harmonics Current	EN61000-3-2


2、 EMS

ESD	EN61000-4-2	Air:8KV Contact:4KV	Criteria A
RS	EN61000-4-3	80MHz~1GHz 3V/m	Criteria A
EFT	EN61000-4-4	5KHz AC=1KV	Criteria A
Surge Test	EN61000-4-5	1.2/50us AC:±2KV 8/50us	Criteria A
CS	EN61000-4-6	0.15MHz-80MHz 3V/m	Criteria A
Voltage dips	EN61000-4-8	30% 10ms 60% 100ms >95% 5000ms	Criteria A
Power Frequency Magnetic Field	EN61000-4-11	50Hz 30A/m	Criteria A
RF Electromagnetic Field pulse modulated	EN550204	900±5MHz 200Hz 3V/m, 50%Duty cycle	Criteria A

六.安装尺寸:

build in dimension


unit: mm





七. 标签:

Spec Label




Connector define




八. 包装:

Packing unit: mm



Inner Box plane



solid

