



ESM-S200 系列概述

一. 电源规格:

电源型号 (MODEL)	输入(VAC)	输出 (VDC)	保护功能 (PROTECTION)	尺寸 (SIZE) MM
ESM-S200S3.3	90-132VAC 176-264VAC	3.3V/40A	SCP /OCP/OVP	200mm*100mm*50mm
ESM-S200S5	90-132VAC 176-264VAC	5V/40A	SCP /OCP/OVP	200mm*100mm*50mm
ESM-S200S7.5	90-132VAC 176-264VAC	7.5V/27A	SCP /OCP/OVP	200mm*100mm*50mm
ESM-S200S12	90-132VAC 176-264VAC	12V/17A	SCP /OCP/OVP	200mm*100mm*50mm
ESM-S200S24	90-132VAC 176-264VAC	24V/8.5A	SCP /OCP/OVP	200mm*100mm*50mm
ESM-S200S28	90-132VAC 176-264VAC	28V/7.5A	SCP /OCP/OVP	200mm*100mm*50mm
ESM-S200S36	90-132VAC 176-264VAC	36V/5.5A	SCP /OCP/OVP	200mm*100mm*50mm
ESM-S200S48	90-132VAC 176-264VAC	48V/4.5A	SCP /OCP/OVP	200mm*100mm*50mm
ESM-S200S63	90-132VAC 176-264VAC	63V/3.2A	SCP /OCP/OVP	200mm*100mm*50mm

二. 系列特征:

Features

- AC input range selectable by switch
- Compact size
- Protections: SCP /OCP/ OVP
- High efficiency
- Low cost, high reliability
- 100% full load burn-in test
- 1 years warranty


三. 产品外观:



net weight: 850g

四. 工作温度, 输出功率曲线:

Temperature- load curve



五. 测试标准:

EMC DATA:

1、 EMI

RE/CE	EN55022 CLASS A
Harmonics Current	EN61000-3-2

2、 EMS

ESD	EN61000-4-2	Air:8KV Contact:4KV	Criteria A
RS	EN61000-4-3	80MHz~1GHz 3V/m	Criteria A
EFT	EN61000-4-4	5KHz AC=1KV	Criteria A
Surge Test	EN61000-4-5	1.2/50us AC:±2KV 8/50us	Criteria A
CS	EN61000-4-6	0.15MHz~80MHz 3V/m	Criteria A
Voltage dips	EN61000-4-8	30% 10ms	





		60% 100ms >95% 5000ms	Criteria A
Power Frequency Magnetic Field	EN61000-4-11	50Hz 30A/m	Criteria A
RF Electromagnetic Field pulse modulated	ENV50204	900±5MHz 200Hz 3V/m, 50%Duty cycle	Criteria A

六. 安装尺寸:

build in dimension


unit: mm





七. 标签:

Spec Label



八. 包装:

Packing unit: mm

