



PFM-U150S 系列概述

一. 电源规格:

电源型号 (MODEL)	输入 (VAC)	输出 (VDC)	保护功能 (PROTECTION)	尺寸 (SIZE) MM
PFM-U150S3.3	100~240VAC	3.3V/33A	SCP/OCP/OVP	200mm × 110mm × 50mm
PFM-U150S5	100~240VAC	5V/30A	SCP/OCP/OVP	200mm × 110mm × 50mm
PFM-U150S12	100~240VAC	12V/12.5A	SCP/OCP/OVP	200mm × 110mm × 50mm
PFM-U150S15	100~240VAC	15V/10A	SCP/OCP/OVP	200mm × 110mm × 50mm
PFM-U150S24	100~240VAC	24V/6.25A	SCP/OCP/OVP	200mm × 110mm × 50mm
PFM-U150S28	100~240VAC	28V/5.5A	SCP/OCP/OVP	200mm × 110mm × 50mm
PFM-U150S36	100~240VAC	36V/4.2A	SCP/OCP/OVP	200mm × 110mm × 50mm
PFM-U150S48	100~240VAC	48V/3.2A	SCP/OCP/OVP	200mm × 110mm × 50mm

二. 系列特性:

Features:

- Universal AC input / Full range
- Compact size
- PF>0.98@115VAC; >0.95@230VAC
- Protections: SCP /OCP/ OVP
- All using 105°C long life electrolytic Capacitors
- Built-in active PFC
- High efficiency, high reliability, high working temperature
- Cooling by free air convection
- 100% full load burn-in test
- 3 years warranty

三. 产品外观:




Net weight 900g




四. 工作温度, 输出功率曲线以及负载曲线图:

Temperature- load curve



Input voltage- load curve



五.测试标准:

EMC DATA:

1、 EMI

RE/CE	EN55022 CLASS A
Harmonics Current	EN61000-3-2

2、 EMS


ESD	EN61000-4-2	Air:8KV Contact:4KV	Criteria A
RS	EN61000-4-3	80MHz~1GHz 3V/m	Criteria A
EFT	EN61000-4-4	5KHz AC=1KV	Criteria A
Surge Test	EN61000-4-5	1.2/50us AC:±2KV 8/50us	Criteria A
CS	EN61000-4-6	0.15MHz-80MHz 3V/m	Criteria A
Voltage dips	EN61000-4-8	30% 10ms 60% 100ms >95% 5000ms	Criteria A
Power Frequency Magnetic Field	EN61000-4-11	50Hz 30A/m	Criteria A
RF Electromagnetic Field pulse modulated	ENV50204	900±5MHz 200Hz 3V/m, 50%Duty cycle	Criteria A



六. 安装尺寸:


build in dimension

unit: mm





七. 标签:



Connector define



八. 包装:

